
AS3531 Series

Double Hex Extended Washer Head, Close Tolerance Machine Bolt

AS3531-3-03	thru	AS3531-3-24	(.1900-32 diameter)
AS3531-4-03	thru	AS3531-4-28	(.2500-28 diameter)
AS3531-5-04	thru	AS3531-5-33	(.3125-24 diameter)
AS3531-6-04	thru	AS3531-6-36	(.3750-24 diameter)
AS3531-7-05	thru	AS3531-7-43	(.4375-20 diameter)
AS3531-8-05	thru	AS3531-8-46	(.5000-20 diameter)
AS3531-9-05	thru	AS3531-9-51	(.5625-18 diameter)
AS351-10-06	thru	AS3531-10-54	(.6250-18 diameter)
AS3531-12-07	thru	AS3531-12-63	(.7500-16 diameter)
AS3531-14-08	thru	AS3531-14-73	(.8750-14 diameter)
AS3531-16-09	thru	AS3531-16-84	(1.0000-12 diameter)

Material:

Alloy Steel – A286

Material Spec:

AMS5853, UNS K66286

Tensile Strength:

160 KSI Min.

Thread Length:

Available in the entire range of standard lengths

Drilling:

Drill Head for Safety Wire

For inquiries or to place an order please call us at 718-847-6321.