

---

## AS3580 Series

---

### Double Hex Head, PD Shank, Close Tolerance Machine Bolt

|              |      |              |                     |
|--------------|------|--------------|---------------------|
| AS3580-3-05  | thru | AS3580-3-62  | (.1900-32 diameter) |
| AS3580-4-06  | thru | AS3580-4-96  | (.2500-28 diameter) |
| AS3580-5-08  | thru | AS3580-5-96  | (.3125-24 diameter) |
| AS3580-6-09  | thru | AS3580-6-96  | (.3750-24 diameter) |
| AS3580-7-11  | thru | AS3580-7-96  | (.4375-20 diameter) |
| AS3580-8-12  | thru | AS3580-8-96  | (.5000-20 diameter) |
| AS3580-9-14  | thru | AS3580-9-96  | (.5625-18 diameter) |
| AS3580-10-13 | thru | AS3580-10-96 | (.6250-18 diameter) |
| AS3580-12-16 | thru | AS3580-12-96 | (.7500-16 diameter) |

---

**Material:**

CRES – Inconel 718

**Material Spec:**

AMS5662, UNS 07718

**Tensile Strength:**

185 KSI Min.

**Thread Length:**

Available in the entire range of standard lengths

*For inquiries or to place an order please call us at 718-847-6321.*