
NASM21250 Series

12 Point, Steel, Flanged, External Wrenching, Tension Bolts

MS21250-02003	thru	MS21250-0296	(.1640-32 diameter)
MS21250-03003	thru	MS21250-0396	(.1900-32 diameter)
MS21250-04003	thru	MS21250-0496	(.2500-28 diameter)
MS21250-05003	thru	MS21250-0596	(.3125-24 diameter)
MS21250-06003	thru	MS21250-0696	(.3750-24 diameter)
MS21250-07003	thru	MS21250-0796	(.4375-20 diameter)
MS21250-08003	thru	MS21250-0896	(.5000-20 diameter)
MS21250-09005	thru	MS21250-09112	(.5625-18 diameter)
MS21250-10005	thru	MS21250-10112	(.6250-18 diameter)
MS21250-12005	thru	MS21250-12112	(.7500-16 diameter)
MS21250-14007	thru	MS21250-14112	(.8750-14 diameter)
MS21250-16007	thru	MS21250-16112	(1.0000-12 diameter)
MS21250-18007	thru	MS21250-18128	(1.1250-12 diameter)
MS21250-20009	thru	MS21250-20128	(1.2500-12 diameter)
MS21250-22009	thru	MS21250-22128	(1.3750-12 diameter)
MS21250-24009	thru	MS21250-24128	(1.5000-12 diameter)

Material:

Alloy Steel – 4140, 4340, 8740

Material Spec:

AMS6382, AMS6415, AMS6484, AMS6322, AMS6325

Tensile Strength:

180 KSI Min.

Hardness:

39-43 HRC

Finish:

Cadmium Plated per AMS-QQ-P-416, TYPE 2, CLASS 2

Drilling Options:

No Hole

example: MS21250-04008

Drill Head for Safety Wire – add “H” (replace hyphen)

example: MS21250H04008

Thread Length:

Available in the entire range of standard lengths

For inquiries or to place an order please call us at 718-847-6321.