

---

## NASM21297 Series

---

### Spline Drive, Steel, External Wrenching, Tension Bolts

MS21297-03003	thru	MS21297-03096	(.1900-32 diameter)
MS21297-04003	thru	MS21297-04096	(.2500-28 diameter)
MS21297-05003	thru	MS21297-05096	(.3125-24 diameter)
MS21297-06003	thru	MS21297-06096	(.3750-24 diameter)
MS21297-07003	thru	MS21297-07096	(.4375-20 diameter)
MS21297-08003	thru	MS21297-08096	(.5000-20 diameter)
MS21297-09003	thru	MS21297-09112	(.5625-18 diameter)
MS21297-10003	thru	MS21297-10112	(.6250-18 diameter)
MS21297-12003	thru	MS21297-12112	(.7500-16 diameter)
MS21297-14003	thru	MS21297-14112	(.8750-14 diameter)
MS21297-16003	thru	MS21297-16112	(1.0000-12 diameter)

---

**Material:**

Alloy Steel – H-11

**Material Spec:**

AMS6487

**Tensile Strength:**

220 KSI Min.

**Hardness:**

45-50 HRC

**Finish:**

Cadmium Coated (Vacuum Deposited) per AMS-C-8837, TYPE 2, CLASS 2

**Drilling Options:**

No Hole

example: MS21297-04016

Drill Head for Safety Wire – add “H” (replace hyphen)

example: MS21297H04016

**Thread Length:**

Available in the entire range of standard lengths

*For inquiries or to place an order please call us at 718-847-6321.*