
NASM24667 Series

Socket Head, Cap, Flat Countersunk, Alloy Steel, Screw

MS24667-1	thru	MS24667-5	(.1120-40 diameter)
MS24667-7	thru	MS24667-11	(.1380-32 diameter)
MS24667-13	thru	MS24667-17	(.1640-32 diameter)
MS24667-19	thru	MS24667-25	(.1900-24 diameter)
MS24667-27	thru	MS24667-35	(.2500-20 diameter)
MS24667-37	thru	MS24667-47	(.3125-18 diameter)
MS24667-49	thru	MS24667-60	(.3750-16 diameter)
MS24667-62	thru	MS24667-71	(.4375-14 diameter)
MS24667-73	thru	MS24667-82	(.5000-13 diameter)
MS24667-84	thru	MS24667-91	(.6250-11 diameter)
MS24667-92	thru	MS24667-100	(.7500-10 diameter)

Material:

Alloy Steel

Material Spec:

See Procurement Specifications

Finish:

Cadmium Plate in accordance with AMS-QQ-P-416, TYPE 2, CLASS 3/6
example: MS24667-1

Zinc Coating in accordance with ASTM B633, TYPE 2, CLASS FE/ZN 5
– add “Z” suffix example: MS24667-1Z

Heat Treatment:

See Procurement Specifications

Locking Element:

Non-Locking Element

example: MS24667-1

Optional Self-Locking Element (either Patch Type or Longitudinal Strip per MIL-DTL-18240)
– add “L” suffix example: MS24667-1L

Recess:

Flat Countersunk

For inquiries or to place an order please call us at 718-847-6321.