
NASM24678 Series

Socket Hex Head, Cap, Alloy Steel, Screw

MS24678-1	thru	MS24678-5	(.1380-40 diameter)
MS24678-6	thru	MS24678-8	(.1640-36 diameter)
MS24678-9	thru	MS24678-18	(.1900-32 diameter)
MS24678-19	thru	MS24678-29	(.2500-28 diameter)
MS24678-30	thru	MS24678-40	(.3125-24 diameter)
MS24678-41	thru	MS24678-52	(.3750-24 diameter)
MS24678-53	thru	MS24678-56	(.4375-20 diameter)
MS24678-57	thru	MS24678-64	(.5000-20 diameter)
MS24678-65	thru	MS24678-70	(.6250-18 diameter)

Material:

Alloy Steel

Material Spec:

See Procurement Specifications

Tensile Strength:

170-180 KSI Min.

Finish:

Cadmium Plate in accordance with AMS-QQ-P-416, TYPE 2, CLASS 3
example: MS24678-1

Aluminum Ion Vapor Deposited per MIL-DTL-83488, TYPE 2, CLASS 3
– add “A” suffix example: MS24678-1A

No Protective Coating – add “U” add suffix
example: MS24678-1U

Drilling:

Drill Head for Safety Wire

Thread Length:

Available in the entire range of standard lengths

For inquiries or to place an order please call us at 718-847-6321.