
NA0036 Series

Hex Head, Alloy Steel, Close Tolerance Aerospace Bolts, Metric

NA0036-050002	thru	NA0036-050050	(MJ5 x 0.8 thread)
NA0036-060004	thru	NA0036-060060	(MJ6 x 1 thread)
NA0036-080004	thru	NA0036-080080	(MJ8 x 1 thread)
NA0036-100006	thru	NA0036-100100	(MJ10 x 1.25 thread)
NA0036-120006	thru	NA0036-120120	(MJ12 x 1.25 thread)
NA0036-140008	thru	NA0036-140140	(MJ14 x 1.5 thread)
NA0036-160008	thru	NA0036-160160	(MJ16 x 1.5 thread)
NA0036-180010	thru	NA0036-180160	(MJ18 x 1.5 thread)
NA0036-200010	thru	NA0036-200160	(MJ20 x 1.5 thread)

Material:

Alloy Steel – 4140, 4340, 8740

Tensile Strength:

160-180 KSI Min.

Hardness:

36-40 HRC

Finish:

Cadmium Plated per AMS-QQ-P-416, TYPE 2, CLASS 2

Heat Treatment Spec:

1100 MPa

Thread Length:

Available in the entire range of standard lengths

Drilling Options:

No Hole

example: NA0036-080016

Drill Threads for Cotter Pin – add “D” (replace hyphen)

example: NA0036D080016

Drill Head for Safety Wire – add “H” (replace hyphen)

example: NA0036H080016

Drill Head for Safety Wire and Drill Threads for Cotter Pin

– add “DH” (replace hyphen) example: NA0036DH080016

For inquiries or to place an order please call us at 718-847-6321.