

---

## NA0059 Series

---

### Spline Drive, CRES, Close Tolerance Aerospace Bolts, Metric

NA0059-050004	thru	NA0059-050050	(MJ5 x 0.8 thread)
NA0059-060004	thru	NA0059-060060	(MJ6 x 1 thread)
NA0059-080004	thru	NA0059-080080	(MJ8 x 1 thread)
NA0059-100006	thru	NA0059-100100	(MJ10 x 1.25 thread)
NA0059-120006	thru	NA0059-120120	(MJ12 x 1.25 thread)
NA0059-140008	thru	NA0059-140140	(MJ14 x 1.5 thread)
NA0059-160008	thru	NA0059-160160	(MJ16 x 1.5 thread)
NA0059-180010	thru	NA0059-180160	(MJ18 x 1.5 thread)
NA0059-200010	thru	NA0059-200160	(MJ20 x 1.5 thread)

---

**Material:**

CRES – A286

**Material Spec:**

AMS5732, AMS5737, UNS 566286

**Finish:**

Passivate per AMS-QQ-P-35

**Heat Treatment Spec:**

1250 MPa

**Thread Length:**

Available in the entire range of standard lengths

**Drilling Options:**

No Hole

example: NA0059-080016

Drill Threads for Cotter Pin – add “**D**” (replace hyphen)

example: NA0059D080016

Drill Head for Safety Wire – add “**H**” (replace hyphen)

example: NA0059H080016

Drill Head for Safety Wire and Drill Threads for Cotter Pin

– add “**DH**” (replace hyphen) example: NA0059DH080016

*For inquiries or to place an order please call us at 718-847-6321.*