
NA0063 Series

Spline Drive, Alloy Steel, Close Tolerance Aerospace Bolts, Metric

NA0063-050004	thru	NA0063-050050	(MJ5 x 0.8 thread)
NA0063-060004	thru	NA0063-060060	(MJ6 x 1 thread)
NA0063-080004	thru	NA0063-080080	(MJ8 x 1 thread)
NA0063-100006	thru	NA0063-100100	(MJ10 x 1.25 thread)
NA0063-120006	thru	NA0063-120120	(MJ12 x 1.25 thread)
NA0063-140008	thru	NA0063-140140	(MJ14 x 1.5 thread)
NA0063-160008	thru	NA0063-160160	(MJ16 x 1.5 thread)
NA0063-180010	thru	NA0063-180160	(MJ18 x 1.5 thread)
NA0063-200010	thru	NA0063-200160	(MJ20 x 1.5 thread)

Material:

Alloy Steel

Material Spec:

AMS6487(H-1), UNS T20811

Hardness:

51-54 HRC

Finish:

Cadmium Plated per MIL-C-8837, TYPE 2, CLASS 2

Heat Treatment Spec:

1800 MPa

Thread Length:

Available in the entire range of standard lengths

Drilling Options:

No Hole

example: NA0063-080016

Drill Head for Safety Wire – add “H” (replace hyphen)

example: NA0063H080016

For inquiries or to place an order please call us at 718-847-6321.