
NAS1102V Series

Flat 100 Degree Head, Titanium, Machine Screws

| | | | |
|---------------|------|----------------|---------------------|
| NAS1102V02-10 | thru | NAS1102V02-100 | (.0860-56 diameter) |
| NAS1102V04-10 | thru | NAS1102V04-100 | (.1120-40 diameter) |
| NAS1102V06-10 | thru | NAS1102V06-100 | (.1380-32 diameter) |
| NAS1102V08-10 | thru | NAS1102V08-100 | (.1640-32 diameter) |
| NAS1102V3-10 | thru | NAS1102V3-100 | (.1900-32 diameter) |
| NAS1102V4-10 | thru | NAS1102V4-100 | (.2500-28 diameter) |
| NAS1102V5-10 | thru | NAS1102V5-100 | (.3125-24 diameter) |
| NAS1102V6-10 | thru | NAS1102V6-100 | (.3750-24 diameter) |

Material:

Titanium – 6Al-4V

Material Spec:

AMS4967

Tensile Strength:

160 KSI Min.

Finish Options:

No Finish

example: NAS1102V02-10

Aluminum Coated per NAS4006 – add “A” suffix

example: NAS1102V02-10A

Aluminum Coated per MIL-C-83488, TYPE 2, CLASS 3 – add “C” suffix

example: NAS1102V02-10C

Thread:

Full Thread

Drive Recess:

Offset Cruciform Recess

For inquiries or to place an order please call us at 718-847-6321.