
NAS1131V thru NAS1138V Series

Pan Head, Titanium, Close Tolerance Machine Screws

NAS1131V10	thru	NAS1131V100	(.1380-32 diameter)
NAS1132V10	thru	NAS1132V100	(.1640-32 diameter)
NAS1133V10	thru	NAS1133V100	(.1900-32 diameter)
NAS1134V10	thru	NAS1134V100	(.2500-28 diameter)
NAS1135V10	thru	NAS1135V100	(.3125-24 diameter)
NAS1136V10	thru	NAS1136V100	(.3750-24 diameter)
NAS1137V10	thru	NAS1137V100	(.4375-20 diameter)
NAS1138V10	thru	NAS1138V100	(.5000-20 diameter)

Material:

Titanium – 6Al-4V

Material Spec:

AMS4967

Tensile Strength:

160 KSI Min.

Finish Options:

None

example: NAS1131V10

Aluminum Coated per NAS4006 – add “A” suffix

example: NAS1131V10A

Aluminum Coated per MIL-C-83488, TYPE 2, CLASS 3 – add “C” suffix

example: NAS1131V10C

Heat Treatment Spec:

AMS2759

Thread:

Short Thread

Recess Options:

None

example: NAS1131V10

Offset Cruciform Recess per MS14191– add “R” suffix

example: NAS1131V10R

For inquiries or to place an order please call us at 718-847-6321.