
NAS1141 thru NAS1148 Series

Modified Pan Head, Alloy Steel, Close Tolerance Machine Screws

NAS1141-10	thru	NAS1141-100	(.1380-32 diameter)
NAS1142-10	thru	NAS1142-100	(.1640-32 diameter)
NAS1143-10	thru	NAS1143-100	(.1900-32 diameter)
NAS1144-10	thru	NAS1144-100	(.2500-28 diameter)
NAS1145-10	thru	NAS1145-100	(.3125-24 diameter)
NAS1146-10	thru	NAS1146-100	(.3750-24 diameter)
NAS1147-10	thru	NAS1147-100	(.4375-20 diameter)
NAS1148-10	thru	NAS1148-100	(.5000-20 diameter)

Material:

Alloy Steel – 4140, 4340, 8740

Material Spec:

MIL-S-5000, MIL-S-5626, MIL-S-6049

Tensile Strength:

160-180 KSI Min.

Finish Options:

Cadmium Plated per QQ-P-416, TYPE 2, CLASS 2

example: NAS1141-10

Cadmium Plated per QQ-P-416, TYPE 2, CLASS 2,

Blackened per Unichrome® Dip per Bulletin P-65-B-Cd – add “B” suffix

example: NAS1141-10B

Heat Treatment Spec:

MIL-H-6875

Thread:

Short Thread

Recess:

Toro-Set® Recess

For inquiries or to place an order please call us at 718-847-6321.