

NAS1151V thru NAS1158V Series

Flat 100 Degree Flush Tension Head, Titanium, Precision Aerospace Screw

| | | | |
|-----------|------|------------|---------------------|
| NAS1151V1 | thru | NAS1151V96 | (.1380-32 diameter) |
| NAS1152V2 | thru | NAS1152V96 | (.1640-32 diameter) |
| NAS1153V2 | thru | NAS1153V96 | (.1900-32 diameter) |
| NAS1154V2 | thru | NAS1154V96 | (.2500-28 diameter) |
| NAS1155V3 | thru | NAS1155V96 | (.3125-24 diameter) |
| NAS1156V4 | thru | NAS1156V96 | (.3750-24 diameter) |
| NAS1157V4 | thru | NAS1157V96 | (.4375-20 diameter) |
| NAS1158V5 | thru | NAS1158V96 | (.5000-20 diameter) |

Material:

Titanium – 6Al-4V

Material Spec:

AMS4967

Tensile Strength:

160 KSI Min.

Finish Options:

No Finish (Clean and Degrease)

example: NAS1151V1

Aluminum Coated per NAS4006 – add “A” suffix

example: NAS1151V1A

Heat Treatment Spec:

MIL-H-6875

Thread Length:

Available in the entire range of standard lengths

Drilling Options:

No Hole

example: NAS1151V1

Drill Shank for Cotter Pin – add “D” (replace hyphen)

example: NAS1151V1D

Drive Option:

Offset Cruciform Recess– add “R” suffix

example: NAS1151V1R

For inquiries or to place an order please call us at 718-847-6321.