

---

## NAS1151 thru NAS1158 Series

---

### Flat 100 Degree Flush Tension Head, Alloy Steel, Precision Aerospace Screw

|           |      |            |                     |
|-----------|------|------------|---------------------|
| NAS1151E1 | thru | NAS1151E96 | (.1380-32 diameter) |
| NAS1152E2 | thru | NAS1152E96 | (.1640-32 diameter) |
| NAS1153E2 | thru | NAS1153E96 | (.1900-32 diameter) |
| NAS1154E2 | thru | NAS1154E96 | (.2500-28 diameter) |
| NAS1155E3 | thru | NAS1155E96 | (.3125-24 diameter) |
| NAS1156E4 | thru | NAS1156E96 | (.3750-24 diameter) |
| NAS1157E4 | thru | NAS1157E96 | (.4375-20 diameter) |
| NAS1158E5 | thru | NAS1158E96 | (.5000-20 diameter) |

---

**Material:**

Alloy Steel – CRES A286

**Material Spec:**

MIL-S-5626, MIL-S-8844, MIL-S-6049

**Tensile Strength:**

160-180 KSI Min.

**Hardness:**

36-40 HRC

**Finish Options:**

Passivated per QQ-P-35, TYPE 1 or TYPE 8 – add “E” (replace hyphen)  
example: NAS1151E1

Aluminum Coated per NAS4006 – add “A” suffix  
example: NAS1151E1A

Cadmium Plated per QQ-P-416, TYPE 2, CLASS 2 – add “P” suffix  
example: NAS1151E1P

**Heat Treatment Spec:**

MIL-H-6875

**Thread Length:**

Available in the entire range of standard lengths

**Drilling Options:**

No Hole  
example: NAS1151E1

Drill Shank for Cotter Pin – add “D” (replace hyphen)  
example: NAS1151E1D

**Drive Option:**

Offset Cruciform Recess– add “R” suffix  
example: NAS1151E1R

*For inquiries or to place an order please call us at 718-847-6321.*