
NAS1161V thru NAS1168V Series

Self-Locking, Flat 100 Degree Head, Titanium, Shear Screws

NAS1161V10	thru	NAS1161V100	(.1380-32 diameter)
NAS1162V10	thru	NAS1162V100	(.1640-32 diameter)
NAS1163V10	thru	NAS1163V100	(.1900-32 diameter)
NAS1164V10	thru	NAS1164V100	(.2500-28 diameter)
NAS1165V10	thru	NAS1165V100	(.3125-24 diameter)
NAS1166V10	thru	NAS1166V100	(.3750-24 diameter)
NAS1167V10	thru	NAS1167V100	(.4375-20 diameter)
NAS1168V10	thru	NAS1168V100	(.5000-20 diameter)

Material:

Titanium – 6Al-4V

Material Spec:

AMS4967

Tensile Strength:

160 KSI Min.

Finish Options:

No Finish (Clean and Degrease)

example: NAS1161V10

Aluminum Coated per NAS4006 – add “A” suffix

example: NAS1161V10A

Heat Treatment Spec:

AMS-H-81200, AMS2801

Thread:

Short Thread

Locking Element Options:

None

example: NAS1161V10

Nylon Strip Type Locking Element – add “L” (suffix)

example: NAS1161V10L

Nylon Pellet Type Locking Element – add “N” (suffix)

example: NAS1161V10N

Nylon Patch Type Locking Element – add “B” (suffix)

example: NAS1161V10B

PCTFE Strip Type Locking Element – add “LK” (suffix)

example: NAS1161V10LK

PCTFE Pellet Type Locking Element – add “NK” (suffix)

example: NAS1161V10NK

PCTFE Optional Locking Element (Applicable for One Torque Cycle) – add “K” (suffix)

example: NAS1161V10K

Polyester Patch Type Locking Element – add “J” (suffix)

example: NAS1161V10J

Recess:

Offset Crusiform Recess

For inquiries or to place an order please call us at 718-847-6321.

FASTENER DIMENSIONS, INC. ISO9001, AS9100 & AS9120 Certified

6850 River Road, Pennsauken, New Jersey 08110

WEB: WWW.FASTDIM.COM • PHONE: 718-847-6321 • FAX: 718-847-8414