

NAS1189V Series

100 Degree Flat Head, Titanium, Aerospace Screw

NAS1189V02-3	thru	NAS1189V02-96	(.0860-56 diameter)
NAS1189V04-3	thru	NAS1189V04-96	(.1120-40 diameter)
NAS1189V06-3	thru	NAS1189V06-96	(.1380-32 diameter)
NAS1189V08-3	thru	NAS1189V08-96	(.1640-32 diameter)
NAS1189V3-3	thru	NAS1189V3-96	(.1900-32 diameter)
NAS1189V4-3	thru	NAS1189V4-96	(.2500-28 diameter)
NAS1189V5-3	thru	NAS1189V5-96	(.3125-24 diameter)
NAS1189V6-3	thru	NAS1189V6-96	(.3750-24 diameter)

Material:

Titanium – 6Al-4V

Material Spec:

AMS4928, AMS4967

Tensile Strength:

160 KSI Min.

Finish Options:

None

example: NAS1189V3-1

Aluminum Coated per NAS4006 – add “A” suffix

example: NAS1189V3-1A

Heat Treatment Spec:

AMS-H-81200, AMS2801

Thread:

Full Thread

Self-Locking Element:

Nylon Strip Type Locking Element – add “L” suffix

example: NAS1189V3T8L

Nylon Pellet Type Locking Element – add “N” suffix

example: NAS1189V3T8N

Nylon Patch Type Locking Element – add “B” suffix

example: NAS1189V3T8B

PCTFE Strip Type Locking Element – add “LK” suffix

example: NAS1189V3T8LK

PCTFE Pellet Type Locking Element – add “NK” suffix

example: NAS1189V3T8NK

Patch Type Polyester Locking Element – add “J” suffix

example: NAS1189V3T8J

Recess Options:

Cruciform Recess per NASM9006

– add “P” (replace hyphen) example: NAS1189V4P8A

Offset Cruciform Recess per NASM33781

– add “T” (replace hyphen) example: NAS1189V4T8A

Ribbed Offset Cruciform Recess per MS14191 (sizes 06 thru 5 inclusive only)

– add “R” (replace hyphen) example: NAS1189V4R8A

For inquiries or to place an order please call us at 718-847-6321.

FASTENER DIMENSIONS, INC. ISO9001, AS9100 & AS9120 Certified

6850 River Road, Pennsauken, New Jersey 08110

WEB: WWW.FASTDIM.COM • PHONE: 718-847-6321 • FAX: 718-847-8414