
NAS1190E Series

Pan Head, CRES, Full Thread, Self-Locking Screw

NAS1190E02-3	thru	NAS1190E02-96	(.0860-56 diameter)
NAS1190E04-3	thru	NAS1190E04-96	(.1120-40 diameter)
NAS1190E06-3	thru	NAS1190E06-96	(.1380-32 diameter)
NAS1190E08-3	thru	NAS1190E08-96	(.1640-32 diameter)
NAS1190E3-3	thru	NAS1190E3-96	(.1900-32 diameter)
NAS1190E4-3	thru	NAS1190E4-96	(.2500-28 diameter)
NAS1190E5-3	thru	NAS1190E5-96	(.3125-24 diameter)
NAS1190E6-3	thru	NAS1190E6-96	(.3750-24 diameter)

Material:

CRES – A286

Material Spec:

AMS5731, AMS5732, AMS5737, AMS5853

Tensile Strength:

160-190 KSI Min.

Finish Options:

Clean and Passivate per AMS-QQ-P-35

example: NAS1190E3-3

Cadmium Plated per QQ-P-416, TYPE 2, CLASS 2 – add “H” suffix

example: NAS1190E3H

Aluminum Coated per NAS4006 – add “A” suffix

example: NAS1190E08T12A

Heat Treatment Spec:

AMS5853

Thread:

Full Thread

Locking Element:

Nylon Strip Type Locking Element – add “L” suffix

example: NAS1190E4-3L

Nylon Pellet Type Locking Element – add “N” suffix

example: NAS1190E4-3N

Nylon Patch Type Locking Element – add “B” suffix

example: NAS1190E4-3B

PCTFE Strip Type Locking Element – add “F” suffix

example: NAS1190E4-3F

PCTFE Pellet Type Locking Element – add “G” suffix

example: NAS1190E4-3G

PCTFE Pellet Type with optional Locking Element – add “K” suffix

example: NAS1190E4-3K

Polyethylene Patch Type Locking Element – add “J” suffix

example: NAS1190E4-3J

Drive Resess:

Cruciform Recess per NASM9006 – add “P” after first dash number

example: NAS1190E4P3

Offset Cruciform Ribbed Recess per NASM14191 – add “R” after first dash number

example: NAS1190E4R3

Offset Cruciform Recess per NASM33781 – add “T” after first dash number

example: NAS1190E4T3

For inquiries or to place an order please call us at 718-847-6321.