

---

## NAS1216\_E Series

---

### Pan Head, Alloy Steel, Hi-Torque Recess, Aerospace Screws

NAS1216-04E1	thru	NAS1216-04E100	(.1120-40 diameter)
NAS1216-06E1	thru	NAS1216-06E100	(.1380-32 diameter)
NAS1216-08E1	thru	NAS1216-08E100	(.1640-32 diameter)
NAS1216-3E1	thru	NAS1216-3E100	(.1900-32 diameter)
NAS1216-4E1	thru	NAS1216-4E100	(.2500-28 diameter)
NAS1216-5E1	thru	NAS1216-5E100	(.3125-24 diameter)
NAS1216-6E1	thru	NAS1216-6E100	(.3750-24 diameter)

---

**Material:**

Alloy Steel – CRES A286

**Material Spec:**

AMS5731, AMS5732, AMS5737, AMS5853

**Tensile Strength:**

160-190 KSI Min.

**Finish Options:**

Clean and Passivated per AMS2700, METHOD 1, CLASS 4

example: NAS1216-04E1

Cadmium Plated per AMS-QQ-P-416, TYPE 2, CLASS 2

– add “P” suffix example: NAS1216-04E1P

**Heat Treatment Spec:**

AMS2759

**Thread Length:**

Full Thread

**Drilling Options:**

No Hole

example: NAS1216-04E1

Drill One Hole through Head for Safety Wire – add “H” suffix

example: NAS1216-04E1H

**Self Locking Options:**

None

example: NAS1216-04E1

Self Locking Patch Lock Type – add “L” suffix

example: NAS1216-04E1L

**Drive Recess:**

Slotted Dove Tail Recess

*For inquiries or to place an order please call us at 718-847-6321.*