
NAS1216 Series

Pan Head, Alloy Steel, Hi-Torque Recess, Aerospace Screws

NAS1216-04-1	thru	NAS1216-04-100	(.1120-40 diameter)
NAS1216-06-1	thru	NAS1216-06-100	(.1380-32 diameter)
NAS1216-08-1	thru	NAS1216-08-100	(.1640-32 diameter)
NAS1216-3-1	thru	NAS1216-3-100	(.1900-32 diameter)
NAS1216-4-1	thru	NAS1216-4-100	(.2500-28 diameter)
NAS1216-5-1	thru	NAS1216-5-100	(.3125-24 diameter)
NAS1216-6-1	thru	NAS1216-6-100	(.3750-24 diameter)

Material:

Alloy Steel – 4140, 4340, 8740

Material Spec:

AMS6382, AMS6415, AMS6484, AMS6322, AMS6325, AMS6327

Tensile Strength:

160-180 KSI Min.

Finish Options:

Cadmium Plated per QQ-P-416, TYPE 2, CLASS 2

example: NAS1216-04-1

Cadmium Plated per QQ-P-416, TYPE 2, CLASS 2 with Dull Black Chromate treatment

– add “B” suffix example: NAS1216-04-1B

Heat Treatment Spec:

AMS2759

Thread Length:

Full Thread

Drilling Options:

No Hole

example: NAS1216-04-1

Drill One Hole through Head for Safety Wire – add “H” suffix

example: NAS1216-04-1H

Self Locking Options:

None

example: NAS1216-04-1

Self Locking Patch Lock Type – add “L” suffix

example: NAS1216-04-1L

Drive Recess:

Slotted Dove Tail Recess

For inquiries or to place an order please call us at 718-847-6321.