
NAS1216_V Series

Pan Head, Titanium, Hi-Torque Recess, Aerospace Screws

NAS1216-04V1	thru	NAS1216-04V100	(.1120-40 diameter)
NAS1216-06V1	thru	NAS1216-06V100	(.1380-32 diameter)
NAS1216-08V1	thru	NAS1216-08V100	(.1640-32 diameter)
NAS1216-3V1	thru	NAS1216-3V100	(.1900-32 diameter)
NAS1216-4V1	thru	NAS1216-4V100	(.2500-28 diameter)
NAS1216-5V1	thru	NAS1216-5V100	(.3125-24 diameter)
NAS1216-6V1	thru	NAS1216-6V100	(.3750-24 diameter)

Material:

Titanium – 6Al-4V

Material Spec:

AMS4928, AMS4967

Tensile Strength:

160 KSI Min.

Finish

None

Heat Treatment Spec:

AMS-H-81200, AMS2801

Thread Length:

Full Thread

Drilling Options:

No Hole

example: NAS1216-04V1

Drill One Hole through Head for Safety Wire – add “H” suffix

example: NAS1216-04V1H

Self Locking Options:

None

example: NAS1216-04V1

Self Locking Patch Lock Type – add “L” suffix

example: NAS1216-04V1L

Drive Recess:

Slotted Dove Tail Recess

For inquiries or to place an order please call us at 718-847-6321.