
NAS1218 Series

Pan Head, Alloy Steel, High Precision Aerospace Machine Bolts

NAS1218-04-1	thru	NAS1218-04-100	(.1120-40 diameter)
NAS1218-06-1	thru	NAS1218-06-100	(.1380-32 diameter)
NAS1218-08-1	thru	NAS1218-08-100	(.1640-32 diameter)
NAS1218-3-1	thru	NAS1218-3-100	(.1900-32 diameter)
NAS1218-4-1	thru	NAS1218-4-100	(.2500-28 diameter)
NAS1218-5-1	thru	NAS1218-5-100	(.3125-24 diameter)
NAS1218-6-1	thru	NAS1218-6-100	(.3750-24 diameter)

Material:

Alloy Steel – 4140, 4340, E4340, 8740

Material Spec:

MIL-S-5000, MIL-S-6049

Tensile Strength:

160-180 KSI Min.

Hardness:

36-40 HRC

Finish:

Cadmium Plated per QQ-P-416, TYPE 2, CLASS 2

Heat Treatment Spec:

MIL-H-6875

Thread Length:

Available in the entire range of standard lengths

Self-Locking Options:

None

example: NAS1218-04-1

Self-Locking Element – add “L” add suffix

example: NAS1218-04-1L

Recess Options:

Dovetail Slot Recess

example: NAS1218-04-1

Offset Cruciform Recess – add “R” (replace hyphen)

example: NAS1218R04-1

For inquiries or to place an order please call us at 718-847-6321.