
NAS1219 Series

100 Degree Flush Head, Alloy Steel, High Precision Aerospace Screws

NAS1219-04E1	thru	NAS1219-04E100	(.1120-40 diameter)
NAS1219-06E1	thru	NAS1219-06E100	(.1380-32 diameter)
NAS1219-08E1	thru	NAS1219-08E100	(.1640-32 diameter)
NAS1219-3E1	thru	NAS1219-3E100	(.1900-32 diameter)
NAS1219-4E1	thru	NAS1219-4E100	(.2500-28 diameter)
NAS1219-5E1	thru	NAS1219-5E100	(.3125-24 diameter)
NAS1219-6E1	thru	NAS1219-6E100	(.3750-24 diameter)

Material:

CRES – A286

Material Spec:

AMS5731, AMS5732, AMS5737

Tensile Strength:

160 KSI Min.

Finish Options:

Passivated per QQ-P-35

Cadmium Plated per QQ-P-416, TYPE 2, CLASS 2 – add “P” suffix

example: NAS1219-04E1P

Heat Treatment Spec:

MIL-H-6875

Thread Length:

Available in the entire range of standard lengths

Self-Locking Options:

None

example: NAS1219-04E1

Self-Locking Element – add “L” add suffix

example: NAS1219-04E1L

Recess:

Dovetail Slot Recess per MS33750

For inquiries or to place an order please call us at 718-847-6321.