

---

## NAS1219 Series

---

### 100 Degree Flush Head, Stainless Steel, High Precision Aerospace Screws

NAS1219-04CR1	thru	NAS1219-04CR100	(.1120-40 diameter)
NAS1219-06CR1	thru	NAS1219-06CR100	(.1380-32 diameter)
NAS1219-08CR1	thru	NAS1219-08CR100	(.1640-32 diameter)
NAS1219-3CR1	thru	NAS1219-3CR100	(.1900-32 diameter)
NAS1219-4CR1	thru	NAS1219-4CR100	(.2500-28 diameter)
NAS1219-5CR1	thru	NAS1219-5CR100	(.3125-24 diameter)
NAS1219-6CR1	thru	NAS1219-6CR100	(.3750-24 diameter)

---

**Material:**

Stainless Steel – CRES 302 or 305

**Material Spec:**

QQ-S-763

**Tensile Strength:**

125 KSI Min.

**Finish:**

Passivated per QQ-P-35

**Heat Treatment Spec:**

MIL-H-6875

**Thread Length:**

Available in the entire range of standard lengths

**Self-Locking Options:**

None

example: NAS1219-04CR1

Self-Locking Element – add “L” add suffix

example: NAS1219-04CR1L

**Recess:**

Dovetail Slot Recess per MS33750

*For inquiries or to place an order please call us at 718-847-6321.*