

---

## NAS1221 Series

---

### 100 Degree Flush Head, Stainless Steel, High Precision Aerospace Bolts

NAS1221-04CR1	thru	NAS1221-04CR96	(.1120-40 diameter)
NAS1221-06CR2	thru	NAS1221-06CR96	(.1380-32 diameter)
NAS1221-08CR2	thru	NAS1221-08CR96	(.1640-32 diameter)
NAS1221-3CR2	thru	NAS1221-3CR96	(.1900-32 diameter)
NAS1221-4CR3	thru	NAS1221-4CR96	(.2500-28 diameter)
NAS1221-5CR3	thru	NAS1221-5CR96	(.3125-24 diameter)
NAS1221-6CR4	thru	NAS1221-6CR96	(.3750-24 diameter)

---

**Material:**

Stainless Steel – CRES 302 or 305

**Material Spec:**

QQ-S-763

**Tensile Strength:**

125 KSI Min.

**Finish:**

Passivated per QQ-P-35

**Heat Treatment Spec:**

MIL-H-6875

**Thread Length:**

Available in the entire range of standard lengths

**Self-Locking Options:**

None

example: NAS1221-04CR1

Self-Locking Element – add “L” add suffix

example: NAS1221-04CR1L

**Recess Options:**

Dovetail Slot Recess per MS33750

example: NAS1221-04CR1

Offset Cruciform Recess per MS14191 – add “R” (replace hyphen)

example: NAS1221R04CR1

*For inquiries or to place an order please call us at 718-847-6321.*