
NAS1221 Series

100 Degree Flush Head, Titanium, High Precision Aerospace Bolts

NAS1221-04V1	thru	NAS1221-04V96	(.1120-40 diameter)
NAS1221-06V2	thru	NAS1221-06V96	(.1380-32 diameter)
NAS1221-08V2	thru	NAS1221-08V96	(.1640-32 diameter)
NAS1221-3V2	thru	NAS1221-3V96	(.1900-32 diameter)
NAS1221-4V3	thru	NAS1221-4V96	(.2500-28 diameter)
NAS1221-5V3	thru	NAS1221-5V96	(.3125-24 diameter)
NAS1221-6V4	thru	NAS1221-6V96	(.3750-24 diameter)

Material:

Titanium – 6Al-4V

Material Spec:

AMS4928, AMS4967

Tensile Strength:

160-180 KSI Min.

Finish:

No Finish (Clean and Degrease)

Heat Treatment Spec:

MIL-H-6875

Thread Length:

Available in the entire range of standard lengths

Self-Locking Options:

None

example: NAS1221-04V1

Self-Locking Element – add “L” add suffix

example: NAS1221-04V1L

Recess Options:

Dovetail Slot Recess per MS33750

example: NAS1221-04V1

Offset Cruciform Recess per MS14191 – add “R” (replace hyphen)

example: NAS1221R04V1

For inquiries or to place an order please call us at 718-847-6321.