
NAS1223 thru NAS1235 Series

Self-Locking Hex Head, Alloy Steel, Aerospace Shear Bolts

NAS1223-1	thru	NAS1223-100	(.1900-32 diameter)
NAS1224-1	thru	NAS1224-100	(.2500-28 diameter)
NAS1225-1	thru	NAS1225-100	(.3125-24 diameter)
NAS1226-1	thru	NAS1226-100	(.3750-24 diameter)
NAS1227-1	thru	NAS1227-100	(.4375-20 diameter)
NAS1228-1	thru	NAS1228-100	(.5000-20 diameter)
NAS1229-1	thru	NAS1229-100	(.5625-18 diameter)
NAS1230-1	thru	NAS1230-100	(.6250-18 diameter)
NAS1231-1	thru	NAS1231-100	(.7500-14 diameter)
NAS1232-1	thru	NAS1232-100	(.8750-14 diameter)
NAS1233-1	thru	NAS1233-100	(1.0000-12 diameter)
NAS1234-1	thru	NAS1234-100	(1.1250-12 diameter)
NAS1235-1	thru	NAS1235-100	(1.2500-12 diameter)

Material:

Alloy Steel per NASM7838

Material Spec:

MIL-S-6758

Tensile Strength:

160-180 KSI Min.

Hardness:

36-40 HRC

Finish:

Cadmium Plated per QQ-P-416, TYPE 2, CLASS 2

example: NAS1226-1

Cadmium Plated per QQ-P-416, TYPE 1 – add “W” suffix

example: NAS1226-1W

Heat Treatment Spec:

AMS2759

Thread Length:

Available in the entire range of standard lengths

No Finish (Clean and Degrease)

Locking Element:

Non-Locking

example: NAS1226-1

Strip Type Locking Element – add “L” suffix

example: NAS1226-1L

Button Type Locking Element – add “N” suffix

example: NAS1226-1N

Patch Type Locking Element – add “P” suffix

example: NAS1226-1P

For inquiries or to place an order please call us at 718-847-6321.

FASTENER DIMENSIONS, INC. ISO9001, AS9100 & AS9120 Certified

6850 River Road, Pennsauken, New Jersey 08110

WEB: WWW.FASTDIM.COM • PHONE: 718-847-6321 • FAX: 718-847-8414