
NAS1223C thru NAS1235C Series

Self-Locking Hex Head, CRES, Aerospace Shear Bolts

NAS1223C1	thru	NAS1223C100	(.1900-32 diameter)
NAS1224C1	thru	NAS1224C100	(.2500-28 diameter)
NAS1225C1	thru	NAS1225C100	(.3125-24 diameter)
NAS1226C1	thru	NAS1226C100	(.3750-24 diameter)
NAS1227C1	thru	NAS1227C100	(.4375-20 diameter)
NAS1228C1	thru	NAS1228C100	(.5000-20 diameter)
NAS1229C1	thru	NAS1229C100	(.5625-18 diameter)
NAS1230C1	thru	NAS1230C100	(.6250-18 diameter)
NAS1231C1	thru	NAS1231C100	(.7500-14 diameter)
NAS1232C1	thru	NAS1232C100	(.8750-14 diameter)
NAS1233C1	thru	NAS1233C100	(1.0000-12 diameter)
NAS1234C1	thru	NAS1234C100	(1.1250-12 diameter)
NAS1235C1	thru	NAS1235C100	(1.2500-12 diameter)

Material:

Alloy Steel – CRES A286

Material Spec:

AMS5731, AMS5732, AMS5737, AMS5853

Tensile Strength:

140 KSI Min.

Hardness:

36-40 HRC

Finish:

No Finish (Clean and Degrease)

Heat Treatment Spec:

AMS2759

Thread Length:

Available in the entire range of standard lengths

Locking Element:

Non-Locking

example: NAS1226C1

Strip Type Locking Element – add “L” suffix

example: NAS1226C1L

Button Type Locking Element – add “N” suffix

example: NAS1226C1N

Patch Type Locking Element – add “P” suffix

example: NAS1226C1P

For inquiries or to place an order please call us at 718-847-6321.

FASTENER DIMENSIONS, INC. ISO9001, AS9100 & AS9120 Certified

6850 River Road, Pennsauken, New Jersey 08110

WEB: WWW.FASTDIM.COM • PHONE: 718-847-6321 • FAX: 718-847-8414