
NAS1253 thru NAS1260 Series

100 Degree Flush Head, Alloy Steel, High Precision Aerospace Bolts

NAS1253-1	thru	NAS1253-100	(.1900-32 diameter)
NAS1254-1	thru	NAS1254-100	(.2500-28 diameter)
NAS1255-1	thru	NAS1255-100	(.3125-24 diameter)
NAS1256-1	thru	NAS1256-100	(.3750-24 diameter)
NAS1257-1	thru	NAS1257-100	(.4375-20 diameter)
NAS1258-1	thru	NAS1258-100	(.5000-20 diameter)
NAS1259-1	thru	NAS1259-100	(.5625-18 diameter)
NAS1260-1	thru	NAS1260-100	(.6250-18 diameter)

Material:

Alloy Steel – 4140, 4340, 6150, 8735, 8740

Material Spec:

AMS6322, AMS6325, AMS6327, AMS6349, AMS6382, AMS6415, AMS6484, AMS-S-5000, AMS6320, AMS6448

Tensile Strength:

160-180 KSI Min.

Hardness:

36-40 HRC

Finish:

Cadmium Plated per QQ-P-416, TYPE 2, CLASS 2

Heat Treatment Spec:

AMS2759

Thread Length:

Available in the entire range of standard lengths

Recess:

Hi-Torque Recess

Oversize:

.0312 Oversize

For inquiries or to place an order please call us at 718-847-6321.