
NAS1271 thru NAS1280 Series

12 Point Head, External Wrenching, Titanium, Precision Aerospace Bolt

NAS1271-4	thru	NAS1271-112	(.2500-28 diameter)
NAS1272-4	thru	NAS1272-96	(.3125-24 diameter)
NAS1273-4	thru	NAS1273-96	(.3750-24 diameter)
NAS1274-4	thru	NAS1274-96	(.4375-20 diameter)
NAS1275-4	thru	NAS1275-96	(.5000-20 diameter)
NAS1276-6	thru	NAS1276-96	(.5625-18 diameter)
NAS1277-6	thru	NAS1277-112	(.6250-18 diameter)
NAS1278-6	thru	NAS1278-112	(.7500-16 diameter)
NAS1279-8	thru	NAS1279-112	(.8750-14 diameter)
NAS1280-8	thru	NAS1280-112	(1.000-12 diameter)

Material:

Titanium – 6Al-4V

Material Spec:

AMS4928, AMS4967

Tensile Strength:

600 KSI Min.

Hardness:

36-40 HRC

Finish:

No Finish (Clean and Degrease)

Heat Treatment Spec:

AMS-H-81200, AMS2801

Thread Length:

Available in the entire range of standard lengths

Drilling Options:

No Hole

example: NAS1271-1

Drill Head for Safety Wire – add “H” suffix

example: NAS1271-1H

For inquiries or to place an order please call us at 718-847-6321.