
NAS1299 Series

100 Degree Philips Flat Head, Alloy Steel, Precision Shoulder Machine Screw

NAS1299-06-1	thru	NAS1299-06-8	(.1380-32 diameter)
NAS1299-3-1	thru	NAS1299-3-11	(.1900-32 diameter)
NAS1299-4-2	thru	NAS1299-4-13	(.2500-28 diameter)
NAS1299-5-2	thru	NAS1299-5-15	(.3125-24 diameter)
NAS1299-6-3	thru	NAS1299-6-18	(.3750-24 diameter)
NAS1299-7-3	thru	NAS1299-7-22	(.4375-20 diameter)

Material:

Alloy Steel – Low Carbon Material Steel conforming to material spec

Material Spec:

AMS6300, MIL-S-6049, MIL-S-6050, MIL-S-6098, MIL-S-6758

Tensile Strength:

125-145 KSI Min.

Hardness:

26-32 HRC

Finish:

Cadmium Plated per QQ-P-416, TYPE 2, CLASS 2

Heat Treatment Spec:

MIL-H-6875

Thread Length:

Available in the entire range of standard lengths

Drilling Options:

No Hole

example: NAS1299-06-1

Drill Shank for Cotter Pin – add “**D**” (replace hyphen)

example: NAS1299-06D1

For inquiries or to place an order please call us at 718-847-6321.