
NAS1300 Series

Thumbscrew

NAS1300-06-1	thru	NAS1300-06-100	(.1380-32 diameter)
NAS1300-08-1	thru	NAS1300-08-100	(.1640-32 diameter)
NAS1300-3-1	thru	NAS1300-3-100	(.1900-32 diameter)
NAS1300-4-1	thru	NAS1300-4-100	(.2500-28 diameter)
NAS1300-5-1	thru	NAS1300-5-100	(.3125-24 diameter)
NAS1300-6-1	thru	NAS1300-6-100	(.3750-24 diameter)
NAS1300-8-1	thru	NAS1300-8-100	(.5000-20 diameter)

Material:

Carbon Steel – see procurement spec

example: NAS1300-06-80

Alloy Steel – CRES per AMS-S-7720, Comp 302 – add “C” (replace hyphen)

example: NAS1300C06-80

Finish:

Steel – Cadmium Plated per QQ-P-416, TYPE 2, CLASS 2

example: NAS1300-06-80

CRES – Passivate per AMS2700, METHOD 1, CLASS 4

example: NAS1300C06-80

Shoulder Option:

Plain

example: NAS1300C8-32

Shouldered – add “T” (replace second hyphen)

example: NAS1300C8T32

Drilling Options:

No Hole

example: NAS1300-06-80

Drill Hole for Safety Wire – add “D” suffix

example: NAS1300C8T32D

For inquiries or to place an order please call us at 718-847-6321.