

---

## NAS1322J thru NAS1326J Series

---

### Threaded, Head, Alloy Steel, Threaded, Shear Pin

NAS1322J1	thru	NAS1322J100	(.1640-32 diameter)
NAS1323J1	thru	NAS1323J100	(.1900-32 diameter)
NAS1324J1	thru	NAS1324J100	(.2500-28 diameter)
NAS1325J1	thru	NAS1325J100	(.3125-24 diameter)
NAS1326J1	thru	NAS1326J100	(.3750-24 diameter)

---

#### Material:

Alloy Steel – H-11

#### Material Spec:

AMS6487

#### Tensile Strength:

260-280 KSI Min.

#### Finish Options:

Nickel Zinc Alloy Plate and Hydrogen Embrittlement Relief per AMS2417  
Interior of Hex to be Painted with Aluminum Silicone Paint and  
the Pin Baked 1 Hour at 350 to 400 degrees.

example: NAS1324-10

Diffused Nickel-Cadmium Plated per AMS2416

– add “P” suffix example: NAS1326J8P

#### Heat Treatment Spec:

NAS1511

#### Shank Option:

.0156 Oversize – add “1” following dash in basic part number

example: NAS1325-1J16

.0312 Oversize – add “2” following dash in basic part number

example: NAS1325-2J16

*For inquiries or to place an order please call us at 718-847-6321.*