
NAS1351 Series

Socket Head Cap, Alloy Steel, High Precision Aerospace Screws

NAS1351-04-1	thru	NAS1351-04-100	(.1120-48 diameter)
NAS1351-06-1	thru	NAS1351-06-100	(.1380-40 diameter)
NAS1351-08-1	thru	NAS1351-08-100	(.1640-36 diameter)
NAS1351-3-1	thru	NAS1351-3-100	(.1900-32 diameter)
NAS1351-4-1	thru	NAS1351-4-100	(.2500-28 diameter)
NAS1351-5-1	thru	NAS1351-5-100	(.3125-24 diameter)
NAS1351-6-1	thru	NAS1351-6-100	(.3750-24 diameter)
NAS1351-7-1	thru	NAS1351-7-100	(.4375-20 diameter)
NAS1351-8-1	thru	NAS1351-8-100	(.5000-20 diameter)
NAS1351-10-1	thru	NAS1351-10-100	(.6250-18 diameter)
NAS1351-12-1	thru	NAS1351-12-100	(.7500-16 diameter)
NAS1351-14-1	thru	NAS1351-14-100	(.8750-14 diameter)
NAS1351-16-1	thru	NAS1351-16-100	(1.0000-12 diameter)

Material:

Alloy Steel – 8740

Material Spec:

MIL-S-5000, MIL-S-5626, MIL-S-6049, MIL-S-6415

Tensile Strength:

170-180 KSI Min.

Hardness:

37-45 HRC

Finish:

Black Oxide in Accordance with MIL-DTL-13924, CLASS 1

Cadmium Plated per QQ-P-416, TYPE 2, CLASS 2 – add “P” suffix

example: NAS1351-04-1P

Heat Treatment Spec:

MIL-H-6875 AMS-H-6875, AS3170

Thread Length:

Available in the entire range of standard lengths

Drilling Options:

No Hole

example: NAS1351-04-1

Drill 2 Holes in Head Spaced 180 Degrees Apart – add “H” (replace hyphen)

example: NAS1351-04H1 thru NAS1351-06H100 only

Drill 6 Holes in Head Spaced 60 Degrees Apart – add “H” (replace hyphen)

example: NAS1351-08H1

Locking Options:

None

example: NAS1351-04-1

Optional Type Locking Element – add “LE” (replace hyphen)

example: NAS1351-04LE1

Longitudinal Strip Locking Element – add “LL” (replace hyphen)

example: NAS1351-04LL1

Pellet Locking Element – add “LN” (replace hyphen)

example: NAS1351-04LN1

Patch Type Locking Element – add “LB” (replace hyphen)

example: NAS1351-04LB1

For inquiries or to place an order please call us at 718-847-6321.