

# NAS1351C Series

## Socket Head Cap, Stainless Steel, High Precision Aerospace Screws

|              |      |                |                      |
|--------------|------|----------------|----------------------|
| NAS1351C04-1 | thru | NAS1351C04-100 | (.1120-48 diameter)  |
| NAS1351C06-1 | thru | NAS1351C06-100 | (.1380-40 diameter)  |
| NAS1351C08-1 | thru | NAS1351C08-100 | (.1640-36 diameter)  |
| NAS1351C3-1  | thru | NAS1351C3-100  | (.1900-32 diameter)  |
| NAS1351C4-1  | thru | NAS1351C4-100  | (.2500-28 diameter)  |
| NAS1351C5-1  | thru | NAS1351C5-100  | (.3125-24 diameter)  |
| NAS1351C6-1  | thru | NAS1351C6-100  | (.3750-24 diameter)  |
| NAS1351C7-1  | thru | NAS1351C7-100  | (.4375-20 diameter)  |
| NAS1351C8-1  | thru | NAS1351C8-100  | (.5000-20 diameter)  |
| NAS1351C10-1 | thru | NAS1351C10-100 | (.6250-18 diameter)  |
| NAS1351C12-1 | thru | NAS1351C12-100 | (.7500-16 diameter)  |
| NAS1351C14-1 | thru | NAS1351C14-100 | (.8750-14 diameter)  |
| NAS1351C16-1 | thru | NAS1351C16-100 | (1.0000-12 diameter) |

### Material:

Stainless Steel – CRES 700 thru 42799, 302, 304, 305, 316, 384

### Material Spec:

ASTM-A-493

### Tensile Strength:

70-80 KSI Min.

### Finish:

Passivated per AMS2700, METHOD 1, TYPE 6 or TYPE 7, CLASS 4

example: NAS1351C04-1

Cadmium Plated per QQ-P-416, TYPE 1, CLASS 2 – add “P” suffix

example: NAS1351C04-1P

Silver Flash per AMS2411 – add “S” suffix

example: NAS1351C04-1S

Passivated per AMS2700, METHOD 2, No Post Treatment – add “G” suffix

example: NAS1351C04-1G

Passivated per AMS2700, METHOD 1, TYPE 2 or TYPE 8, CLASS 4, No Post Treatment

– add “M” suffix example: NAS1351C04-1M

### Heat Treatment Spec:

MIL-H-6875, AMS-H-6875, AS2759

### Thread Length:

Available in the entire range of standard lengths

### Drilling Options:

No Hole

example: NAS1351C04-1

Drill 2 Holes in Head Spaced 180 Degrees Apart – add “H” (replace hyphen)

example: NAS1351C04H1 thru NAS1351C06H100 only

Drill 6 Holes in Head Spaced 60 Degrees Apart – add “H” (replace hyphen)

example: NAS1351C08H1

### Locking Options:

None

example: NAS1351C04-1

Optional Type Locking Element – add “LE” (replace hyphen)

example: NAS1351C04LE1

Longitudinal Strip Locking Element – add “LL” (replace hyphen)

example: NAS1351C04LL1

Pellet Locking Element – add “LN” (replace hyphen)

example: NAS1351C04LN1

Patch Type Locking Element – add “LB” (replace hyphen)

example: NAS1351C04LB1

*For inquiries or to place an order please call us at 718-847-6321.*