

NAS1351N Series

Socket Head Cap, Heat Resistant Steel, Precision Aerospace Screws

NAS1351N04-1	thru	NAS1351N04-100	(.1120-48 diameter)
NAS1351N06-1	thru	NAS1351N06-100	(.1380-40 diameter)
NAS1351N08-1	thru	NAS1351N08-100	(.1640-36 diameter)
NAS1351N3-1	thru	NAS1351N3-100	(.1900-32 diameter)
NAS1351N4-1	thru	NAS1351N4-100	(.2500-28 diameter)
NAS1351N5-1	thru	NAS1351N5-100	(.3125-24 diameter)
NAS1351N6-1	thru	NAS1351N6-100	(.3750-24 diameter)
NAS1351N7-1	thru	NAS1351N7-100	(.4375-20 diameter)
NAS1351N8-1	thru	NAS1351N8-100	(.5000-20 diameter)
NAS1351N10-1	thru	NAS1351N10-100	(.6250-18 diameter)
NAS1351N12-1	thru	NAS1351N12-100	(.7500-16 diameter)
NAS1351N14-1	thru	NAS1351N14-100	(.8750-14 diameter)
NAS1351N16-1	thru	NAS1351N16-100	(1.0000-12 diameter)

Material:

CRES – A286

Material Spec:

AMS5731, AMS5732

Tensile Strength:

160 KSI Min.

Hardness:

37-55 HRC

Finish Options:

Passivated per AMS2700, METHOD 1, TYPE 2 or TYPE 8, CLASS 4

example: NAS1351N04-1

Cadmium Plated per QQ-P-416, TYPE 2, CLASS 2 – add “P” suffix

example: NAS1351N04-1P

Silver Flash per AMS2411 – add “S” suffix

example: NAS1351N04-1S

Passivated per AMS2700, METHOD 2, No Post Treatment – add “G” suffix

example: NAS1351N04-1G

Passivated per AMS2700, METHOD 1, TYPE 2 or TYPE 8, CLASS 4, No Post Treatment

– add “M” suffix example: NAS1351N04-1M

Black Oxide in Accordance with MIL-DTL-13924, CLASS 3 – add “B” suffix

example: NAS1351N04-1B

Heat Treatment Spec:

MIL-H-6875, AMS-H-6875, AS2759

Thread Length:

Available in the entire range of standard lengths

Drilling Options:

No Hole

example: NAS1351N04-1

Drill 2 Holes in Head Spaced 180 Degrees Apart – add “H” (replace hyphen)

example: NAS1351N04H1 thru NAS1351N06H100 only

Drill 6 Holes in Head Spaced 60 Degrees Apart – add “H” (replace hyphen)

example: NAS1351N08H1

Locking Options:

None

example: NAS1351N-04-1

Optional Type Locking Element – add “LE” (replace hyphen)

example: NAS1351N04LE1

Longitudinal Strip Locking Element – add “LL” (replace hyphen)

example: NAS1351N04LL1

Pellet Locking Element – add “LN” (replace hyphen)

example: NAS1351N04LN1

Patch Type Locking Element – add “LB” (replace hyphen)

example: NAS1351N04LB1

For inquiries or to place an order please call us at 718-847-6321.