
NAS1352C Series

Socket Head Cap, Alloy Steel, High Precision Aerospace Screws

NAS1352C4-1	thru	NAS1352C4-100	(.2500-20 diameter)
NAS1352C5-1	thru	NAS1352C5-100	(.3125-18 diameter)
NAS1352C6-1	thru	NAS1352C6-100	(.3750-16 diameter)
NAS1352C7-1	thru	NAS1352C7-100	(.4375-14 diameter)
NAS1352C8-1	thru	NAS1352C8-100	(.5000-13 diameter)
NAS1352C10-1	thru	NAS1352C10-100	(.6250-11 diameter)
NAS1352C12-1	thru	NAS1352C12-100	(.7500-10 diameter)
NAS1352C14-1	thru	NAS1352C14-100	(.8750-9 diameter)
NAS1352C16-1	thru	NAS1352C16-100	(1.0000-8 diameter)
NAS1352C20-1	thru	NAS1352C20-100	(1.2500-7 diameter)
NAS1352C24-1	thru	NAS1352C24-100	(1.5000-6 diameter)

Material:

CRES – 300, 302, 304, 305, 316, 384

Material Spec:

ASTM-A-493

Tensile Strength:

70-80 KSI Min.

Hardness:

37-45 HRC

Finish:

Passivated per AMS2700, METHOD 1, TYPE 6 or TYPE 7, CLASS 4

Cadmium Plated per QQ-P-416, TYPE 1, CLASS 2 – add “P” suffix

example: NAS1351C4-1P

Passivated per AMS2700, METHOD 2 - No Post Treatment – add “M” suffix

example: NAS1351C4-1M

Silver Flash in accordance with AMS2411 – add “S” suffix

example: NAS1351C4-1S

Passivated per AMS2700, METHOD 1, TYPE 8, CLASS 4 - No Post Treatment

– add “G” suffix example: NAS1351C4-1G

Heat Treatment Spec:

MIL-H-6875 AMS-H-6875, AS2759

Thread Length:

Available in the entire range of standard lengths

Drilling Options:

No Hole

example: NAS1352C4-1

Drill 6 Holes in Head Spaced 60 Degrees Apart – add “H” (replace hyphen)

example: NAS1352C4H1

Locking Options:

None

example: NAS1352C4-1

Optional Type Locking Element – add “LE” (replace hyphen)

example: NAS1352C4LE1

Longitudinal Strip Locking Element – add “LL” (replace hyphen)

example: NAS1352C4LL1

Pellet Locking Element – add “LN” (replace hyphen)

example: NAS1352C4LN1

Patch Type Locking Element – add “LB” (replace hyphen)

example: NAS1352C4LB1

For inquiries or to place an order please call us at 718-847-6321.