
NAS1503 thru NAS1510 Series

100 Degree Flush Head, Alloy Steel, High Precision Aerospace Bolts

NAS1503-2	thru	NAS1503-96	(.1900-32 diameter)
NAS1504-3	thru	NAS1504-96	(.2500-28 diameter)
NAS1505-3	thru	NAS1505-96	(.3125-24 diameter)
NAS1506-4	thru	NAS1506-96	(.3750-24 diameter)
NAS1507-4	thru	NAS1507-96	(.4375-20 diameter)
NAS1508-4	thru	NAS1508-96	(.5000-20 diameter)
NAS1509-5	thru	NAS1509-96	(.5625-18 diameter)
NAS1510-5	thru	NAS1510-96	(.6250-18 diameter)

Material:

Alloy Steel – 4140, 4340, 6150, 8735, 8740

Material Spec:

AMS6322, AMS6325, AMS6327, AMS6349, AMS6382, AMS6415, AMS6484, AMS-S-5000, AMS6320, AMS6448

Tensile Strength:

160-180 KSI Min.

Hardness:

36-40 HRC

Finish:

Cadmium Plated per QQ-P-416, TYPE 2, CLASS 2

Heat Treatment Spec:

AMS2759

Thread Length:

Available in the entire range of standard lengths

Drive Recess:

Hi-Torque Recess

For inquiries or to place an order please call us at 718-847-6321.