
NAS1578C Series

Flat Pan Head, Alloy Steel, High Precision Aerospace Bolts

NAS1578C3-2 thru NAS1578C3-96 (.1900-32 diameter)
NAS1578C4-2 thru NAS1578C4-96 (.2500-28 diameter)
NAS1578C5-4 thru NAS1578C5-96 (.3125-24 diameter)
NAS1578C6-4 thru NAS1578C6-96 (.3750-24 diameter)
NAS1578C7-4 thru NAS1578C7-96 (.4375-20 diameter)
NAS1578C8-4 thru NAS1578C8-96 (.5000-20 diameter)

Material:

Alloy Steel – CRES A286

Material Spec:

AMS5731, AMS5732, AMS5737, AMS5853

Tensile Strength:

160-190 KSI Min.

Hardness:

36-40 HRC

Finish:

Passivated per QQ-P-35
example: NAS1578C3-1

Cadmium Plated per QQ-P-416, TYPE 2, CLASS 2 – add “P” suffix
example: NAS1578C3-1P

Heat Treatment Spec:

AMS5853

Thread Length:

Available in the entire range of standard lengths

Drive Options:

None

example: NAS1578C3-1

Slotted Dovetail Recess – add “H” (replace hyphen)

example: NAS1578C3H1

Offset Cruciform Recess – add “R” (replace hyphen)

example: NAS1578C3R1

Self-Locking Options:

None

example: NAS1578C3-1

Self-Locking Element – add “L” add suffix

example: NAS1578C3-1L

For inquiries or to place an order please call us at 718-847-6321.

FASTENER DIMENSIONS, INC. ISO9001, AS9100 & AS9120 Certified

6850 River Road, Pennsauken, New Jersey 08110

WEB: WWW.FASTDIM.COM • PHONE: 718-847-6321 • FAX: 718-847-8414