
NAS1578V Series

Flat Pan Head, Titanium, High Precision Aerospace Bolts

NAS1578V3-2	thru	NAS1578V3-96	(.1900-32 diameter)
NAS1578V4-2	thru	NAS1578V4-96	(.2500-28 diameter)
NAS1578V5-4	thru	NAS1578V5-96	(.3125-24 diameter)
NAS1578V6-4	thru	NAS1578V6-96	(.3750-24 diameter)
NAS1578V7-4	thru	NAS1578V7-96	(.4375-20 diameter)
NAS1578V8-4	thru	NAS1578V8-96	(.5000-20 diameter)

Material:

Titanium – 6Al-4V

Material Spec:

AMS4928, AMS4967

Tensile Strength:

160-190 KSI Min.

Hardness:

36-40 HRC

Finish:

No Finish (Clean and Degrease)

Heat Treatment Spec:

AMS4928

Thread Length:

Available in the entire range of standard lengths

Drive Options:

None

example: NAS1578V3-1

Slotted Dovetail Recess – add “H” (replace hyphen)

example: NAS1578V3H1

Offset Cruciform Recess – add “R” (replace hyphen)

example: NAS1578V3R1

Self-Locking Options:

None

example: NAS1578V3-1

Self-Locking Element – add “L” add suffix

example: NAS1578V3-1L

For inquiries or to place an order please call us at 718-847-6321.