

---

## NAS1579C Series

---

### Flat Pan Head, Full Thread, Alloy Steel, High Precision Aerospace Bolts

NAS1579C3-1 thru NAS1579C3-100 (.1900-32 diameter)

NAS1579C4-1 thru NAS1579C4-100 (.2500-28 diameter)

NAS1579C5-1 thru NAS1579C5-100 (.3125-24 diameter)

NAS1579C6-1 thru NAS1579C6-100 (.3750-24 diameter)

---

**Material:**

Alloy Steel – CRES A286

**Material Spec:**

AMS5737

**Tensile Strength:**

160-180 KSI Min.

**Hardness:**

36-40 HRC

**Finish:**

Passivated per QQ-P-35

example: NAS1579C3-1

Cadmium Plated per QQ-P-416, TYPE 2, CLASS 2 – add “P” suffix

example: NAS1579C3-1P

**Heat Treatment Spec:**

AMS2759

**Thread Length:**

Available in the entire range of standard lengths

**Drive Options:**

None

example: NAS1579C3-1

Hi-Torque Recess – add “H” (replace hyphen)

example: NAS1579C3H1

Torq-Set Recess – add “T” (replace hyphen)

example: NAS1579C3T1

*For inquiries or to place an order please call us at 718-847-6321.*