

---

## NAS1579A Series

---

### Flat Pan Head, Full Thread, Alloy Steel, High Precision Aerospace Bolts

NAS1579A3-1 thru NAS1579A3-100 (.1900-32 diameter)  
NAS1579A4-1 thru NAS1579A4-100 (.2500-28 diameter)  
NAS1579A5-1 thru NAS1579A5-100 (.3125-24 diameter)  
NAS1579A6-1 thru NAS1579A6-100 (.3750-24 diameter)

---

**Material:**

Alloy Steel – 4140, 4340, 6150, 8735, 8740

**Material Spec:**

AMS6349, AMS6382, AMS6415, AMS6484, AMS-S-5000, AMS6322,  
AMS6325, AMS6327, AMS6320, AMS6544

**Tensile Strength:**

160-180 KSI Min.

**Hardness:**

36-40 HRC

**Finish:**

Cadmium Plated per QQ-P-416, TYPE 2, CLASS 2

**Heat Treatment Spec:**

AMS2759

**Thread Length:**

Available in the entire range of standard lengths

**Drive Options:**

None

example: NAS1579A3-1

Hi-Torque Recess – add “H” (replace hyphen)

example: NAS1579A3H1

Torq-Set Recess – add “T” (replace hyphen)

example: NAS1579A3T1

*For inquiries or to place an order please call us at 718-847-6321.*