
NAS1581K Series

100 Degree Flush Reduced Head, Titanium, Precision Aerospace Bolts

NAS1581K3_2	thru	NAS1581K3_96	(.1900-32 diameter)
NAS1581K4_2	thru	NAS1581K4_96	(.2500-28 diameter)
NAS1581K5_3	thru	NAS1581K5_96	(.3125-24 diameter)
NAS1581K6_4	thru	NAS1581K6_96	(.3750-24 diameter)
NAS1581K7_4	thru	NAS1581K7_96	(.4375-20 diameter)
NAS1581K8_4	thru	NAS1581K8_96	(.5000-20 diameter)
NAS1581K9_6	thru	NAS1581K9_96	(.5625-18 diameter)
NAS1581K10_6	thru	NAS1581K10_96	(.6250-18 diameter)

Material:

Titanium – 6Al-4V

Material Spec:

AMS4928, AMS4967

Tensile Strength:

160 KSI Min.

Finish Options:

No Finish (Clean and Degrease)

example: NAS1581K3H1

Aluminum Coated per NAS4006, No CLASS – add “G” suffix

example: NAS1581K3H1G

Heat Treatment Spec:

AMS2801

Thread Length:

Available in the entire range of standard lengths

Drive Options:

Slotted Dovetail Recess – add “H” (replace hyphen)

example: NAS1581K3H1

Ribbed Offset Cruciform Recess – add “R” (replace hyphen)

example: NAS1581K3R1

Offset Cruciform Recess – add “T” (replace hyphen)

example: NAS1581K3T1

Shank Options:

.0156 Oversize – add “X” suffix

example: NAS1581K3_1X

.0312 Oversize – add “Y” suffix

example: NAS1581K3_1Y

For inquiries or to place an order please call us at 718-847-6321.