
NAS1582A Series

100 Degree Flush Tension Head, Alloy Steel, Full Thread, Precision Aerospace Bolts

NAS1582A3-1 thru NAS1582A3-100 (.1900-32 diameter)

NAS1582A4-1 thru NAS1582A4-100 (.2500-28 diameter)

NAS1582A5-1 thru NAS1582A5-100 (.3125-24 diameter)

NAS1582A6-1 thru NAS1582A6-100 (.3750-24 diameter)

Material:

Alloy Steel – 4140, 4340, 6150, 8735, 8740

Material Spec:

AMS6320, AMS6322, AMS6325, AMS6327, AMS6150, AMS6349, AMS6382, AMS6415, AMS6484, AMS-S-5000

Tensile Strength:

160-180 KSI Min.

Hardness:

36-40 HRC

Finish:

Cadmium Plated per QQ-P-416, TYPE 2, CLASS 2

Heat Treatment Spec:

AMS2759

Thread Length:

Available in the entire range of standard lengths

Drive Options:

No Recess

example: NAS1582A3-1

Hi-Torque Recess – add “H” (replace hyphen)

example: NAS1582A3H1

Torque-Set Recess – add “T” (replace hyphen)

example: NAS1582A3T1

For inquiries or to place an order please call us at 718-847-6321.