
NAS1586 Series

Double Hex Head, CRES Alloy, High Precision Aerospace Bolts

NAS1586-4-4	thru	NAS1586-4-56	(.2500-28 diameter)
NAS1586-5-4	thru	NAS1586-5-64	(.3125-24 diameter)
NAS1586-6-4	thru	NAS1586-6-72	(.3750-24 diameter)
NAS1586-7-4	thru	NAS1586-7-80	(.4375-20 diameter)
NAS1586-8-4	thru	NAS1586-8-80	(.5000-20 diameter)
NAS1586-9-6	thru	NAS1586-9-96	(.5625-18 diameter)
NAS1586-10-6	thru	NAS1586-10-96	(.6250-18 diameter)
NAS1586-12-8	thru	NAS1586-12-96	(.7500-16 diameter)
NAS1586-14-8	thru	NAS1586-14-96	(.8750-14 diameter)
NAS1586-16-10	thru	NAS1586-16-96	(1.0000-12 diameter)
NAS1586-18-18	thru	NAS1586-18-96	(1.1250-12 diameter)
NAS1586-20-18	thru	NAS1586-20-96	(1.2500-12 diameter)

Material:

Alloy Steel – CRES U-212

Material Spec:

NAS1597

Tensile Strength:

185 KSI Min.

Hardness:

40-46 HRC

Finish:

Clean and Passivate per MIL-S-5002

Heat Treatment Spec:

NAS1597

Thread Length:

Available in the entire range of standard lengths

Drilling Options:

No Hole

example: NAS1586-4-1

Drill 4 Holes through Head for Safety Wire – add “H” (replace hyphen)

example: NAS1586-4H1

For inquiries or to place an order please call us at 718-847-6321.