
NAS1588 Series

Shear Hex Head, Alloy Steel, Precision Aerospace Bolts

NAS1588-3-4	thru	NAS1588-3-50	(.1900-32 diameter)
NAS1588-4-4	thru	NAS1588-4-56	(.2500-28 diameter)
NAS1588-5-4	thru	NAS1588-5-64	(.3125-24 diameter)
NAS1588-6-4	thru	NAS1588-6-72	(.3750-24 diameter)
NAS1588-7-4	thru	NAS1588-7-80	(.4375-20 diameter)
NAS1588-8-4	thru	NAS1588-8-80	(.5000-20 diameter)
NAS1588-9-6	thru	NAS1588-9-96	(.5625-18 diameter)
NAS1588-10-6	thru	NAS1588-10-96	(.6250-18 diameter)
NAS1588-12-8	thru	NAS1588-12-96	(.7500-16 diameter)
NAS1588-14-8	thru	NAS1588-14-96	(.8750-14 diameter)
NAS1588-16-10	thru	NAS1588-16-96	(1.0000-12 diameter)

Material:

Alloy Steel – CRES A286

Material Spec:

NAS1597

Tensile Strength:

140-185 KSI Min.

Hardness:

40-46 HRC

Finish:

Clean and Passivate per MIL-S-5002

Heat Treatment Spec:

NAS1597

Thread Length:

Available in the entire range of standard lengths

For inquiries or to place an order please call us at 718-847-6321.