
NAS1603 thru NAS1610 Series

Flush Head, Alloy Steel, Precision Aerospace Bolts

NAS1603-2	thru	NAS1603-100	(.1900-32 diameter)
NAS1604-3	thru	NAS1604-100	(.2500-28 diameter)
NAS1605-3	thru	NAS1605-100	(.3125-24 diameter)
NAS1606-3	thru	NAS1606-100	(.3750-24 diameter)
NAS1607-5	thru	NAS1607-100	(.4375-20 diameter)
NAS1608-5	thru	NAS1608-100	(.5000-20 diameter)
NAS1609-5	thru	NAS1609-100	(.5625-18 diameter)
NAS1610-5	thru	NAS1610-100	(.6250-18 diameter)

Material:

Alloy Steel – 4140, 4340, 8740

Material Spec:

MIL-S-5000, MIL-S-5626, MIL-S-6049

Tensile Strength:

160-180 KSI Min.

Hardness:

36-40 HRC

Finish:

Cadmium Plated per QQ-P-416, TYPE 2, CLASS 2

Heat Treatment Spec:

MIL-H-6875

Thread Length:

Available in the entire range of standard lengths

Drive Options:

Slotted Dovetail Recess

example: NAS1603-1

Offset Cruciform Recess – add “**R**” (replace hyphen)

example: NAS1603-1R

Shank:

.0312 Oversize

For inquiries or to place an order please call us at 718-847-6321.