
NAS1703 thru NAS1710 Series

Flush Head, Alloy Steel, Precision Aerospace Bolts

NAS1703-2	thru	NAS1703-100	(.1900-32 diameter)
NAS1704-3	thru	NAS1704-100	(.2500-28 diameter)
NAS1705-3	thru	NAS1705-100	(.3125-24 diameter)
NAS1706-3	thru	NAS1706-100	(.3750-24 diameter)
NAS1707-5	thru	NAS1707-100	(.4375-20 diameter)
NAS1708-5	thru	NAS1708-100	(.5000-20 diameter)
NAS1709-5	thru	NAS1709-100	(.5625-18 diameter)
NAS1710-5	thru	NAS1710-100	(.6250-18 diameter)

Material:

Alloy Steel – 4140, 4340, 8740

Material Spec:

MIL-S-5000, MIL-S-5626, MIL-S-6049

Tensile Strength:

160-180 KSI Min.

Hardness:

36-40 HRC

Finish:

Cadmium Plated per QQ-P-416, TYPE 2, CLASS 2

Heat Treatment Spec:

MIL-H-6875

Thread Length:

Available in the entire range of standard lengths

Drive Options:

Slotted Dovetail Recess

example: NAS1703-1

Offset Cruciform Recess – add “**R**” (replace hyphen)

example: NAS1703-1R

Shank:

.0156 Oversize

For inquiries or to place an order please call us at 718-847-6321.