

---

## NAS1767C Series

---

### Close-Tolerance 100 Degree Reduced Head, Alloy Steel, Aerospace Bolts

NAS1767C3-1	thru	NAS1767C3-100	(.1900-32 diameter)
NAS1767C4-1	thru	NAS1767C4-100	(.2500-28 diameter)
NAS1767C5-1	thru	NAS1767C5-100	(.3125-24 diameter)
NAS1767C6-1	thru	NAS1767C6-100	(.3750-24 diameter)
NAS1767C7-1	thru	NAS1767C7-100	(.4375-20 diameter)
NAS1767C8-1	thru	NAS1767C8-100	(.5000-20 diameter)
NAS1767C9-1	thru	NAS1767C9-100	(.5625-18 diameter)
NAS1767C10-1	thru	NAS1767C10-100	(.6250-18 diameter)

---

**Material:**

Alloy Steel – CRES A286

**Material Spec:**

AMS5731, AMS5732, AMS5737

**Tensile Strength:**

160 Ftu Min.

**Hardness:**

36-40 HRC

**Finish Options:**

Passivated per QQ-P-35

example: NAS1767C3-1

Aluminum Coated per NAS4006 – add “A” suffix

example: NAS1767C3-1A

Dry Film Lubricant per MIL-L-8937 – add “L” suffix

example: NAS1767C3-1L

Cadmium Plated per QQ-P-416, TYPE 1, CLASS 2 – add “P” suffix

example: NAS1767C3-1P

**Heat Treatment Spec:**

AMS2759

**Thread Length:**

Available in the entire range of standard lengths

**Drilling Options:**

None

example: NAS1767C3-1

Drill Shank in Threads for Cotter Pin – add “D” suffix

example: NAS1767C3-1D

**Shank Options:**

.0156 Oversize – add “X” suffix

example: NAS1767C3-1X

.0312 Oversize – add “Y” suffix

example: NAS1767C3-1Y

*For inquiries or to place an order please call us at 718-847-6321.*