
NAS1767 Series

Close-Tolerance 100 Degree Reduced Head, Alloy Steel, Aerospace Bolts

NAS1767-3-1	thru	NAS1767-3-100	(.1900-32 diameter)
NAS1767-4-1	thru	NAS1767-4-100	(.2500-28 diameter)
NAS1767-5-1	thru	NAS1767-5-100	(.3125-24 diameter)
NAS1767-6-1	thru	NAS1767-6-100	(.3750-24 diameter)
NAS1767-7-1	thru	NAS1767-7-100	(.4375-20 diameter)
NAS1767-8-1	thru	NAS1767-8-100	(.5000-20 diameter)
NAS1767-9-1	thru	NAS1767-9-100	(.5625-18 diameter)
NAS1767-10-1	thru	NAS1767-10-100	(.6250-18 diameter)

Material:

Alloy Steel – 4140, 4340, 8740

Material Spec:

MIL-S-5000, MIL-S-5626, MIL-S-6049

Tensile Strength:

160-180 KSI Min.

Hardness:

36-40 HRC

Finish Options:

Cadmium Plated per QQ-P-416, TYPE 2, CLASS 2

example: NAS1767-3-1

Aluminum Coated per NAS4006 – add “A” suffix

example: NAS1767-3-1A

Dry Film Lubricant per MIL-L-8937 – add “L” suffix

example: NAS1767-3-1L

Heat Treatment Spec:

AMS2759

Thread Length:

Available in the entire range of standard lengths

Drilling Options:

None

example: NAS1767-3-1

Drill Shank in Threads for Cotter Pin – add “D” suffix

example: NAS1767-3-1D

Shank Options:

.0156 Oversize – add “X” suffix

example: NAS1767-3-1X

.0312 Oversize – add “Y” suffix

example: NAS1767-3-1Y

For inquiries or to place an order please call us at 718-847-6321.

FASTENER DIMENSIONS, INC. ISO9001, AS9100 & AS9120 Certified

6850 River Road, Pennsauken, New Jersey 08110

WEB: WWW.FASTDIM.COM • PHONE: 718-847-6321 • FAX: 718-847-8414