
NAS1767V Series

Close-Tolerance 100 Degree Reduced Head, Titanium, Aerospace Bolts

NAS1767V3-1	thru	NAS1767V3-100	(.1900-32 diameter)
NAS1767V4-1	thru	NAS1767V4-100	(.2500-28 diameter)
NAS1767V5-1	thru	NAS1767V5-100	(.3125-24 diameter)
NAS1767V6-1	thru	NAS1767V6-100	(.3750-24 diameter)
NAS1767V7-1	thru	NAS1767V7-100	(.4375-20 diameter)
NAS1767V8-1	thru	NAS1767V8-100	(.5000-20 diameter)
NAS1767V9-1	thru	NAS1767V9-100	(.5625-18 diameter)
NAS1767V10-1	thru	NAS1767V10-100	(.6250-18 diameter)

Material:

Titanium – 6Al-4V

Material Spec:

AMS4928, AMS4967

Tensile Strength:

160 KSI Min.

Finish Options:

No Finish (Clean and Degrease)

example: NAS1767V3-1

Aluminum Coated per NAS4006, No CLASS – add “A” suffix

example: NAS1767V3-1A

Dry Film Lubricant per MIL-L-8937 – add “L” suffix

example: NAS1767V3-1L

Heat Treatment Spec:

AMS2759

Thread Length:

Available in the entire range of standard lengths

Drilling Options:

None

example: NAS1767V3-1

Drill Shank in Threads for Cotter Pin – add “D” suffix

example: NAS1767V3-1D

Shank Options:

.0156 Oversize – add “X” suffix

example: NAS1767V3-1X

.0312 Oversize – add “Y” suffix

example: NAS1767V3-1Y

For inquiries or to place an order please call us at 718-847-6321.

FASTENER DIMENSIONS, INC. ISO9001, AS9100 & AS9120 Certified

6850 River Road, Pennsauken, New Jersey 08110

WEB: WWW.FASTDIM.COM • PHONE: 718-847-6321 • FAX: 718-847-8414